



1066-POT



RC (BSPT)

- Tapered 1:16
- General purpose applications

RC (BSPT)

- Kegelform 1:16
- Für universelle Anwendungen

RC (BSPT)

- Conicità 1:16
- Per applicazioni generali

RC (BSPT)

- Conicité 1:16
- Pour applications générales

RC (BSPT)

- Konicitet 1:16
- Til generelt brug

RC (BSPT)

- Konisk 1:16
- För diverse applikationer



RC (BSPT)

- Conicidad 1:16
- Para aplicación general

RC (BSPT)

- Уклон 1:16
- Общего назначения

GO TO
LIVE
STOCK
CHECK



EDP	RC(BSPT)	P	L	l	d	a	ZΔ	Stock	Price
22608384	1/8	28	52	15	8,0	6,30	3	○	
22608394	1/4	19	67	19	10,0	8,00	4	○	
22608404	3/8	19	75	21	12,50	10,00	4	○	
22608414	1/2	14	87	26	16,00	12,50	4	○	
22608434	3/4	14	96	28	20,00	16,00	4	○	
22608454	1	11	109	33	25,00	20,00	4	○	

ZΔ= Number of flutes - Anzahl Schneiden - Numero di denti - Nombre de lèvres
 Antal skær - Antal skär - Numero de ranuras - Число режущих кромок

Applications - Anwendungen - Applicazioni - Applications - Applikation - Applikation - Aplicaciones - Применение												
C≤0.2%	0.25<C≤0.4%	C≥0.45%	SCM	25-35 HRC	35-45 HRC	45-52 HRC	52-62 HRC	SUS	SKD	SC	GG	GGG
⊙ 15-24 m/min	⊙ 10-15 m/min	⊙ 8-13 m/min	⊙ 10-15 m/min	○ 7-11 m/min				⊙ 8-16 m/min	○ 10-15 m/min	○ 10-15 m/min		○ 10-15 m/min
Cu	BS	BsC	PB	Al	AC,ADC	MC	ZDC	Ti	Ni	Plast.	Vinyl	