



G (BSP)

High performance forming tap



G (BSP)

Hochleistungsgewindeformer



G (BSP)

Maschio a rullare ad alta performance



G (BSP)

Taraud à refoulé à haute performance



G (BSP)

Yüksek performans ovalama klavuzu



G (BSP)

High Performance rulletap



G (BSP)

High performance pressgångstapp



G (BSP)

Alta prestaciones, macho de laminación




G (BSP)

Высокопроизводительные накатные метчики



G (BSP)

Wysoka wydajność wygniatania gwintów



G (BSP)

G (BSP)

EDP	G	P	L	l	d	a	Drill Hole Size	ZΔ	Stock	Price
48064838	1/8	28	90	9	7	5,5	9,24 ~ 9,35	8	●	
48064839	1/4	19	100	13	11	9	12,41 ~ 12,62	8	●	
48064840	3/8	19	100	13	12	9	15,92 ~ 16,12	8	●	
48064841	1/2	14	125	18	16	12	19,93 ~ 20,15	8	●	

ZΔ= Number of flutes - Anzahl Schneiden - Numero di denti - Nombre de lèvres - Liczba ostrzy
 Antal skær - Antal skär - Numero de ranuras - Число режущих кромок - Kanal sayısı

Applications - Anwendungen - Applicazioni - Applications - Applikation - Applikation - Aplicaciones - Применение - Uygulama - Zastosowania												
C≤0.2%	0.25<C≤0.4%	C≥0.45%	SCM	25-35 HRC	35-45 HRC	45-52 HRC	52-62 HRC	SUS	SKD	SC	GG	GGG
⊙ 15-40 m/min	⊙ 15-40 m/min	⊙ 15-30 m/min	⊙ 15-30 m/min	⊙ 5-20 m/min				⊙ 8-20 m/min		○ 15-40 m/min		
Cu	BS	BsC	PB	Al	AC,ADC	MC	ZDC	Ti	Ni	Plast.	Vinyl	
⊙ 10-30 m/min	⊙ 10-30 m/min	⊙ 10-30 m/min		⊙ 20-50 m/min	⊙ 20-40 m/min		○ 10-30 m/min					